

TRUBLUE GUIDE

CHOOSE THE TRUBLUE FOR YOU

EVERYDAY CLIMBING

SPEED CLIMBING

TRUBLUE XL

TRUBLUE

TRUBLUE SPEED

webbing options

WALL HEIGHT

20 m
66 ft

16 m
53 ft

12 m
39 ft

8 m
26 ft

4 m
13 ft

0 m
0 ft

20 m
purple



20 m
65.6 ft
max.

12 m
39.5 ft
min.

12.5 m
blue



12.5 m
41 ft
max.

7.5 m
24.6 ft
min.

7.5 m
red



7.5 m
24.6 ft
max.

3.5 m
11.5 ft
min.

12.5 m
black



12.5 m
41 ft
max.

7.5 m
24.6 ft
min.

16 m
blue



16 m
52.5 ft
max.

12 m
39.5 ft
min.

USER WEIGHT RANGE

min.

10 kg
22 lbs



max.

150 kg
330 lbs



TESTED



TRUSTED



TRU



mounting is measured from nozzle to ground

CONNECTORS TO CONSIDER

GYM & REC

Climbing Walls




Triple Action Carabiner

Steel Standard
Aluminum Highly Corrosive Environments

FUN CLIMBS

Amusement Climbs

Anti-Release Connectors



Self Belay Belay Mate

ADVENTURE

Aerial Adventure



Swivel S

Dual Connection Continuous Belay

ACCESSORIES



BELAY GATE

A simple way to reinforce the proper use of auto belay devices and minimize the potential risk from climber error.



MOUNTING KIT

Use this turnkey kit for single-point mounting of your TRUBLUE Auto Belay.



UNIVERSAL MOUNT

Designed specifically for use as a climbing anchor.



SCUFF GUARD

Protects both your wall and your TRUBLUE Auto Belay Device.

SAFETY STANDARDS

American National Standard ANSI/ASSE Z359.4-2007: "Safety Requirements for Assisted-Rescue and Self-Rescue Systems, Subsystems and Components" and Devices

Canadian Standard, CSA Z259.2.3-99: "Descent Control Devices"

Australian and New Zealand Standard, AS/NZS 1891.3 1997: "Industrial fall-arrest systems and devices - Part 3: Fall arrest devices"

European Union Directive BS EN 341: "Personal protection equipment against falls from a height - Descender devices"